




Product Description: mPro™ Adjustable IP65 Dimmable Fire Rated Downlight

Fixed, integrated, fire rated 6W LED downlight with unique convertible design to fit ceiling voids as shallow as 47mm. Incorporated miniaturised NanoDrive™ power supply. Available in 2700K, 3000K and 4000K, mPro™ delivers up to 107lm/W making it the most efficient fire rated downlight on the market. Interchangeable bezels available in White, Matt White, Polished Chrome and Satin Nickel. FastRFix™ rapid install system connector included for faster installation. Rated to 30, 60 and 90 minute fire ceilings.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
AU-MPRO2AMW/30	6	3000	610	102	60	Matt White	Triac Dimmable
AU-MPRO2AMW/40	6	4000	640	107	60	Matt White	Triac Dimmable
AU-MPRO2APC/30	6	3000	610	102	60	Polished Chrome	Triac Dimmable
AU-MPRO2APC/40	6	4000	640	107	60	Polished Chrome	Triac Dimmable
AU-MPRO2ASN/30	6	3000	610	102	60	Satin Nickel	Triac Dimmable
AU-MPRO2ASN/40	6	4000	640	107	60	Satin Nickel	Triac Dimmable
AU-MPRO2AW/30	6	3000	610	102	60	White	Triac Dimmable
AU-MPRO2AW/40	6	4000	640	107	60	White	Triac Dimmable

Line Drawing




Polar Curve


Color




Matt White



Polished
Chrome



Satin Nickel



White

Product Features:

- LEDchroic™ lens provides halogen appearance with LED efficiency, anti-glare and precise beam control
- Unique convertible design to fit ceiling voids as shallow as 46mm
- Delivering up to 107lm/W
- Interchangeable IP65 bezels for fixed version providing a sleek finish
- IP65 rated for adjustable and baffle option
- FastRFix™ rapid install system connector included
- 60° beam angle for uniform light distribution
- Tested in 30, 60 and 90 minute solid timber joist fire rated ceilings
- 5 Year Warranty

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.80	IP Rating	IP65
Lifetime L70 (hrs)	40000	Height (mm)	100
Overall Diameter (mm)	98	Cutout Diameter (mm)	85
Product Type	Downlights, Fire-Rated Downlight	Operating Temp. (Min) °C	-20°C
Operating Temp. (Max) °C	45°C		

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.