

Product Description:

The IP65 LinearPac™ LED anti-corrosive has been upgraded up to a market leading 120lm/W providing up to 50% energy savings compared to traditional fluorescent. A highly efficient solution for both interior and exterior applications, it is designed for car parks, service areas, warehouses or retail environments.

Product Image:




LinearPac™ 1200mm 40W IP65 LED Anti-Corrosive


Product Features:

- IP65 vandal resistant polycarbonate body and diffuser
- Efficacy of up to 114lm/W
- Anti-tamper stainless steel clips supplied as standard
- Clip in gear tray for ease of installation and maintenance
- Multiple drill-out conduit entry points end and rear for quick and easy installation
- Supplied with 2 x IP rated cable glands
- Microwave sensor detection range up to 14 metres
- Adjustable light detector from 2-50 lux
- Adjustable hold time 5 seconds to 15 minutes
- IK08 impact rating
- 1.0kV surge protection
- 3 year warranty

Line Drawing Image



Polar Curve Image



Product Specs:

| | | | |
|-------------------------------|-------------|-------------------------------|---------|
| Technology | LED | Number of LEDs | 240 |
| Luminaire Distribution | Direct | Lifetime L70 (hrs) | 30000 |
| Input Voltage | 220~240V AC | Input Frequency | 50/60HZ |
| Dimmable | No | Dali | No |
| IP Rating | IP65 | IK Rating | IK08 |
| Operating Env. Temp. (Min) °C | -20 | Operating Env. Temp. (Max) °C | 40 |
| Optic Material | PC | Power Factor | 0.95 |
| Lamp Base | None | Height (mm) | 80 |
| Length (mm) | 1270 | Width (mm) | 118 |
| Surge Protection (kV) | 1.0 | SDCM | 6 |

SKU Table and Ordering

| SKU Code | Wattage | Lumens | Lumens/Watt | Colour | Beam Angle | Ra | SDCM |
|------------------|---------|--------|-------------|--------|------------|----|------|
| EN-ANT1240B/40 | 40 | 4400 | 110 | 4000 | 120 | 80 | 6 |
| EN-ANT1240BEM/40 | 40 | 4400 | 110 | 4000 | 120 | 80 | 6 |
| EN-ANT1240BMS/40 | 40 | 4400 | 110 | 4000 | 120 | 80 | 6 |

Compliance & Approvals:



Warranty

This product has a warranty period of 3 Years. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

UK Enlite Sales & Distribution
Apex Park
6 Little Burrow
Welwyn Garden City AL7 4SW
United Kingdom
Tel : +44 (0) 1707 35 18 20