




Product Description: CurveE™ 7W Baffled Dimmable IP44 Downlight


Introducing the stylish CurveE™ LED downlight range, this low glare downlight has a sleek baffled design with the light source recessed back to reduce glare. Available in matt white these triac dimmable downlights are an ideal non-fire rated solution for hospitality and residential applications in areas where fire rating is not required.

| SKU Code | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour | SKU Type |
|-----------------|---------|--------|--------|-------------|------------|---------------|----------------|
| EN-DLB072D/30 | 7 | 3000 | 575 | 83 | 60 | Matt White | Triac Dimmable |
| EN-DLB072D/40 | 7 | 4000 | 615 | 88 | 60 | Matt White | Triac Dimmable |
| EN-DLB072DDA/30 | 7 | 3000 | 575 | 83 | 60 | Matt White | DALI Dimmable |
| EN-DLB072DDA/40 | 7 | 4000 | 615 | 88 | 60 | Matt White | DALI Dimmable |
| EN-DLB072DV/30 | 7 | 3000 | 575 | 83 | 60 | Matt White | 1-10V Dimmable |
| EN-DLB072DV/40 | 7 | 4000 | 615 | 88 | 60 | Matt White | 1-10V Dimmable |


Line Drawing



Polar Curve



Color



Matt White

Product Features:

- Baffled design for low glare - LED recessed by 10mm or 20mm
- Plug and play remote driver for easy installation
- IP44 rated - ideal for hospitality and residential applications such as corridors, living areas, bedrooms, dining rooms and zone 2 of bathrooms
- UGR19 (Unified Glare Rating)
- 1.5kV surge protection
- 3 year warranty

Product Specs:

| | | | |
|--------------------------|-------------|--------------------------|------------|
| Input Voltage | 220~240V AC | Power Factor | 0.90 |
| IP Rating | IP44 | Lifetime L70 (hrs) | 25000 |
| Lamp Base | None | Height (mm) | 65 |
| Overall Diameter (mm) | 85 | Weight (Kg) | 0.280 |
| Cutout Diameter (mm) | 72 | Product Type | Downlights |
| Operating Temp. (Min) °C | -20°C | Operating Temp. (Max) °C | 45°C |

Compliance & Approvals:



Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.