

### **Product Features:**

- New and improved loop in/out terminal block for quick and easy installation
- Designed and tested to meet Fire Rating Standards (30, 60, 90-minute fire rated ceilings) for safety and reassurance: BS EN 1365-2: 2014
- Designed and tested to meet acoustic rating standards for reduced sound transmission between separating floors: BS EN ISO 10140-2: 2010 & BS EN ISO 10140-3: 2010 + A1: 2015
- 3 year warranty

# **Product Image:**




EFD™ GU10 IP65 Aluminium Fire Rated Downlight

## **Product Specs:**

| Lamp Type             | GU10        | Lamp Base              | GU10   |
|-----------------------|-------------|------------------------|--------|
| Input Voltage         | 240~240V AC | Positional Adjustment  | Fixed  |
| Input Frequency       | 50/60HZ     | Luminaire Distribution | Direct |
| Positional Adjustment | Fixed       | IP Rating              | IP65   |
| Fire Protection       | Yes         | Acoustic Rated         | Yes    |
| Overall Diameter (mm) | 86          | Cutout Diameter (mm)   | 75     |
| Recess Depth (mm)     | 130         | Weight (Kg)            | 0.314  |

#### **Line Drawing**



### **SKU Table and Ordering:**

| Cat No.(SKU Code) | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour   |
|-------------------|---------|--------|--------|-------------|------------|-----------------|
| EN-FD103PC        |         |        |        |             |            | Polished Chrome |
| EN-FD103PC/30     | 5       | 3000   | 500    | 100         | 60         | Polished Chrome |
| EN-FD103PC/40     | 5       | 4000   | 520    | 104         | 60         | Polished Chrome |
| EN-FD103SN        |         |        |        |             |            | Satin Nickel    |
| EN-FD103SN/30     | 5       | 3000   | 500    | 100         | 60         | Satin Nickel    |
| EN-FD103SN/40     | 5       | 4000   | 520    | 104         | 60         | Satin Nickel    |
| EN-FD103W         |         |        |        |             |            | White           |
| EN-FD103W/30      | 5       | 3000   | 500    | 100         | 60         | White           |
| EN-FD103W/40      | 5       | 4000   | 520    | 104         | 60         | White           |

# **Compliance & Approvals:**













## Warranty:

This product has a guarantee period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.