

AALED1/WV/CCT/PC

Astro CCT 1 Photocell White



Features

All polycarbonate multi-purpose LED square bulkhead suitable for ancillary areas and industrial applications Push fit feed-in, feed-out terminals for speed and ease of installation Internal CCT selector switch allows the installer to choose the CCT between 3000K and 4000K Supplied c/w optional trim attachment which provides a more commercially aesthetic appearance Unique Visiluxe diffuser allows 90% light transmission from LED source for increased performance Instant light output and unlimited switching



General Information

Lamp Type	LED
Colour / Finish	White / Visiluxe
Photocell	Yes
IP Rating	IP65
IK Rating	IK08
Class Protection	2
Internal / External	Internal / External
Surface / Recessed / Suspended	Surface
Lifetime (Hrs)	L80 B50 60,000h
Lifetime (Hrs) Warranty (Years)	L80 B50 60,000h 5
Warranty (Years)	5
Warranty (Years) CE Mark	5 Yes
Warranty (Years) CE Mark Length (mm)	5 Yes 200 mm



Technical Information

Wattage	4W - 7W
Lumens Delivered	520lm - 880lm (4000K)
Lm/W	125lm/W (4000K)
Beam Angle	115
CRI	80
ССТ	3000/4000K
Input	220/240V
Hertz	50/60Hz
Operating Temp	-10°C to 25°C
SDCM	6

Datasheet generated from https://onetimepim.com last updated Thursday, October 6, 2022 8:27:07 AM





