



Calinor EVO Floodlight PIR Warm White 20W Black



- Compact, slim and robust designed LED floodlight suitable for residential and commercial applications
- Polycarbonate front trim provides excellent corrosion resistance
- Toughened microprism glass for visual comfort, uniformity and durability
- Bracket design allows installation without removing mounting bracket
- Pre-wired with 1 metre of rubber insulated cable for ease of installation and easy integration with Floodbox accessory
- Breather gland acts to minimise risk of water ingress
- Polycarbonate spike accessory allowing installation into lawn and garden applications
- PIR versions complete with manual override facility
- Non-dimmable

Features

Feature 1	Compact, slim and robust designed LED floodlight suitable for residential and commercial applications
Feature 2	Polycarbonate front trim provides excellent corrosion resistance
Feature 3	Toughened microprism glass for visual comfort, uniformity and durability
Feature 4	Bracket design allows installation without removing mounting bracket



Feature 5	Pre-wired with 1 metre of rubber insulated cable for ease of installation and easy integration with Floodbox accessory
Feature 6	Breather gland acts to minimise risk of water ingress
Feature 7	Polycarbonate spike accessory allowing installation into lawn and garden applications
Feature 8	PIR versions complete with manual override facility
Feature 9	Non-dimmable
General Information	
Lamp Type	LED
Photocell	Yes
IP Rating	IP65
IK Rating	IK06
Class Protection	1
Internal / External	External
Surface / Recessed / Suspended	Surface
Warranty (Years)	5
Material	Aluminium, Polycarbonate
Technical Information	
Wattage	20W
Lumens Delivered	2000lm
Lm/W	103lm/W
Beam Angle	100
CRI	80
CCT	3000K
Input	220/240V
Hertz	50/60Hz
Operating Temp	-15°C - 40°C
Lumen Depreciation	L80 69,000h
Power Factor	0.5



