



## **AECLED/W/CCT/CF/M3**

Eclipse MultiLED CCT Corridor Function Emergency White



## **Features**

LED wall/ceiling luminaire with adjustable power and light output option suitable for education and commercial applications and ancillary areas

One product with integral driver dip-switch

Internal CCT selector switch allows the installer to choose the CCT between 3000K, 4000K and 6500K

Corridor function options available for effective reduction in energy consumption

Spun aluminium base with dished opal Visiluxe diffuser

BESA box fixing versatile mounting options

Option of white, chrome or satin chrome housing

# General Information

Lamp Type	LED
Colour / Finish	White
Dimmable	Yes
Emergency	Yes
Self Test	Yes
Integral Microwave Sensor	Yes
Bluetooth Enabled	Yes
IP Rating	IP20
IK Rating	IK08
Class Protection	1
Internal / External	Internal
Surface / Recessed / Suspended	Surface
Lifetime (Hrs)	L70 54,000h
Warranty (Years)	5
CE Mark	Yes
Diameter (mm)	435 mm
Depth (mm)	100 mm

# Technical Information

---

<b>Wattage</b>	11W - 25W
<b>Lumens Delivered</b>	1200lm - 2800lm (4000K)
<b>Lm/W</b>	108lm/W - 114lm/W (4000K)
<b>Beam Angle</b>	110
<b>CRI</b>	80
<b>CCT</b>	3000/4000K
<b>Input</b>	220/240V
<b>Hertz</b>	50/60Hz
<b>Operating Temp</b>	0°C to 25°C
<b>SDCM</b>	6

---

Datasheet generated from <https://onetimepim.com> last updated Thursday, October 13, 2022 10:02:22 PM



