



## **AERMLED2/60/CW**

Endurance TP(a) 600x600 Panel Warm White



## **Features**

LED panel suitable for education, commercial and ancillary area applications

Cool white, warm white and daylight options

White anodised aluminium frame for visual compatibility with ceiling grid

Self-Test Panel Pod and Sensor Pod compatible

Surface mounting frame option

Powered by Tridonic

TPa as standard

## General Information

Lamp Type	LED
Colour / Finish	White
Bluetooth Enabled	Yes
IP Rating	IP44
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed, Surface, Suspended
Diffuser Rating	Tp(a)
Lifetime (Hrs)	L80 B10 50,000h
Warranty (Years)	5
CE Mark	Yes
Length (mm)	595 mm
Width (mm)	595 mm
Depth (mm)	10 mm
Accessories	AERMLD/SK, AERMLD/60/SMF, AERMLD/60/CGCB/KIT, APRK/60

# Technical Information

<b>Wattage</b>	30W
<b>Lumens Delivered</b>	3100lm
<b>Lm/W</b>	103lm/W
<b>Beam Angle</b>	110
<b>CRI</b>	80
<b>CCT</b>	4000K
<b>Input</b>	220/240V
<b>Hertz</b>	50/60Hz
<b>Operating Temp</b>	-20°C to 40°C
<b>SDCM</b>	6
<b>UGR</b>	21

Datasheet generated from <https://onetimepim.com> last updated Thursday, October 6, 2022 8:27:16 AM



