



## **AERMLED3/120/DL**

Endurance TP(a) UGR<19 1200x600 Panel Daylight



## **Features**

LED panel suitable for education, commercial and ancillary area applications

UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort

Cool white, warm white and daylight options

White anodised aluminium frame for visual compatibility with ceiling grid

Low glare and even light distribution for multiple applications

Surface mounting frame option

Powered by Tridonic

TPa as standard

## General Information

Lamp Type	LED
Colour / Finish	White
Bluetooth Enabled	Yes
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed, Surface
Diffuser Rating	Tp(a)
Lifetime (Hrs)	L80 B10 50,000h
Warranty (Years)	5
CE Mark	Yes
Length (mm)	1,195 mm
Width (mm)	595 mm
Depth (mm)	10 mm
Accessories	AERMLD/120/SMF, APRK/120

# Technical Information

<b>Wattage</b>	60W
<b>Lumens Delivered</b>	5400lm
<b>Lm/W</b>	90lm/W
<b>Beam Angle</b>	80
<b>CRI</b>	80
<b>CCT</b>	6000K
<b>Input</b>	220/240V
<b>Hertz</b>	50/60Hz
<b>Operating Temp</b>	-20°C to 40°C
<b>SDCM</b>	6
<b>UGR</b>	17

Datasheet generated from <https://onetimepim.com> last updated Thursday, October 6, 2022 8:27:16 AM



