



## **AERMLED3/60/CW**

Endurance TP(a) UGR<19 600x600 Panel Cool White



## **Features**

Edgelit LED panel suitable for education, commercial and ancillary area applications

UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort

Cool white, warm white and daylight options

White anodised aluminium frame for visual compatibility with ceiling grid

Low glare and even light distribution for multiple applications

TPa as standard

Surface mounting frame option

Powered by Tridonic

# General Information

<b>Lamp Type</b>	LED
<b>Colour / Finish</b>	White
<b>Bluetooth Enabled</b>	Yes
<b>IP Rating</b>	IP44
<b>Class Protection</b>	2
<b>Internal / External</b>	Internal
<b>Surface / Recessed / Suspended</b>	Recessed, Surface, Suspended
<b>Diffuser Rating</b>	Tp(a)
<b>Lifetime (Hrs)</b>	L80 B10 50,000h
<b>Warranty (Years)</b>	5
<b>CE Mark</b>	Yes
<b>Length (mm)</b>	595 mm
<b>Width (mm)</b>	595 mm
<b>Depth (mm)</b>	10 mm
<b>Accessories</b>	AERMLD/SK, AERMLD/60/SMF, AERMLD/60/CGCB/KIT, APRK/60

# Technical Information

<b>Wattage</b>	32W
<b>Lumens Delivered</b>	3300lm
<b>Lm/W</b>	104lm/W
<b>Beam Angle</b>	80
<b>CRI</b>	80
<b>CCT</b>	4000K
<b>Input</b>	220/240V
<b>Hertz</b>	50/60Hz
<b>Operating Temp</b>	-20°C to 40°C
<b>SDCM</b>	6
<b>UGR</b>	17

Datasheet generated from <https://onetimepim.com> last updated Thursday, September 29, 2022 10:03:13 PM



