



AERMLED3/60/DL

Endurance TP(a) UGR<19 600x600 Panel Daylight



Features

Edgelit LED panel suitable for education, commercial and ancillary area applications

UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort

Cool white, warm white and daylight options

White anodised aluminium frame for visual compatibility with ceiling grid

Low glare and even light distribution for multiple applications

TPa as standard

Surface mounting frame option

Powered by Tridonic

General Information

Lamp Type	LED
Colour / Finish	White
Bluetooth Enabled	Yes
IP Rating	IP44
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed, Surface, Suspended
Diffuser Rating	Tp(a)
Lifetime (Hrs)	L80 B10 50,000h
Warranty (Years)	5
CE Mark	Yes
Length (mm)	595 mm
Width (mm)	595 mm
Depth (mm)	10 mm
Accessories	AERMLD/SK, AERMLD/60/SMF, AERMLD/60/CGCB/KIT, APRK/60

Technical Information

Wattage	30W
Lumens Delivered	3000lm
Lm/W	98lm/W
Beam Angle	80
CRI	80
CCT	6000K
Input	220/240V
Hertz	50/60Hz
Operating Temp	-20°C to 40°C
SDCM	6
UGR	17

Datasheet generated from <https://onetimepim.com> last updated Thursday, October 13, 2022 10:04:49 PM



