



AFALED/3NM/ST/IP65/B

Falcon Surface Emergency Downlight IP65 Non-Maintained Black



Features

Compact surface ultra-low profile recessed self-test emergency downlight

Supplied with open area and escape route interchangeable lenses

High specification optic design and performance allows increased spacing providing reduced cost

Available in black and white finishes

Up to 19.6 metres spacing between luminaires

Self-test as standard

BESA mounting option

General Information

Lamp Type	LED
Colour / Finish	Black
Emergency	Yes
Self Test	Yes
IP Rating	IP65
IK Rating	IK08
Class Protection	1
Internal / External	Internal / External
Surface / Recessed / Suspended	Surface
Lifetime (Hrs)	L70 50,000h
Warranty (Years)	5
CE Mark	Yes
Length (mm)	165 mm
Width (mm)	165 mm
Height (mm)	57.2 mm
Accessories	ASBP/14/LI

Technical Information

Wattage	3W
Lumens Delivered	Open area - 153lm Escape route - 145lm
Beam Angle	Open area - 96 / Escape route - 135x15
CRI	70
CCT	6500K
Input	220/240V
Hertz	50/60Hz
Operating Temp	0°C to 40°C
SDCM	6

Datasheet generated from <https://onetimepim.com> last updated Thursday, October 6, 2022 8:27:02 AM



