



AGALED/M3

Galaxy CCT MultiLED Downlight Emergency



Features

Multi-wattage compact IP65 LED performance downlight suitable for education, commercial and healthcare applications

Cut-out dimensions suitable to replace most PLC downlights

Fitting and driver pre-wired with ST18 connectors

Faceted reflector and optical fresnel lens provides outstanding performance, uniformity and glare control

Removable twist on, twist off bezel provides option of utilising alternative bezel and drop glass accessories

Dimmable and Emergency options

Powered by Philips

General Information

Lamp Type	LED
Colour / Finish	White
Emergency	Yes
Bluetooth Enabled	Yes
IP Rating	IP65
IK Rating	IK06
Class Protection	2
Bathroom Zone	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lifetime (Hrs)	L80 B50 36,000h
Warranty (Years)	5
CE Mark	Yes
Diameter (mm)	226 mm
Height (mm)	70 mm
Accessories	AGPL/DG1/W, AGPL/DG3/W

Technical Information

Wattage	11W - 16W
Lumens Delivered	1440lm - 2000lm (4000K)
Lm/W	131lm/W - 125lm/W (4000K)
Beam Angle	100
CRI	80
CCT	3000/4000K
Input	220/240V
Hertz	50/60Hz
Operating Temp	-20°C to 35°C
SDCM	5
UGR	24

Datasheet generated from <https://onetimepim.com> last updated Thursday, October 13, 2022 10:05:45 PM



