



AGELED4

Gemini CCT Surface/Suspended Linear 1200mm



Features

High specification fully enclosed linear luminaire suitable for most commercial and educational applications

Push pin release design feature ensures a quick and easy installation

Microprism diffuser for enhanced photometric performance

Robust steel construction

Integral switches for multiple wattages and selectable CCT

CCT selectable between 3000K and 4000K

Suitable for surface and suspension

Powered by Philips

General Information

Lamp Type	LED
Colour / Finish	White
IP Rating	IP20
IK Rating	IK07
Class Protection	1
Internal / External	Internal
Surface / Recessed / Suspended	Surface,Suspended
Lifetime (Hrs)	L70 B50 54,000h
Warranty (Years)	5
CE Mark	Yes
Length (mm)	1,250 mm
Width (mm)	180 mm
Height (mm)	55 mm
Accessories	ASK1

Technical Information

Wattage	21W - 35W
Lumens Delivered	2900lm - 4700lm (4000K)
Lm/W	135lm/W (4000K)
Beam Angle	70
CRI	80
CCT	3000/4000K
Input	220/240V
Hertz	50/60Hz
Operating Temp	-20°C to 50°C
SDCM	3
UGR	18

Datasheet generated from <https://onetimepim.com> last updated Wednesday, December 21, 2022 9:17:28 AM



