



## **ALODLED/110/WW**

Lodi Slim Downlight 110 Warm White



### **Features**

Economic circular LED performance downlight suitable for semi-commercial and residential applications

Low profile design with integral driver

Ideal for use in areas with shallow ceiling voids

Supplied pre-wired with 300mm of cable

## General Information

---

|                                       |                 |
|---------------------------------------|-----------------|
| <b>Lamp Type</b>                      | LED             |
| <b>Colour / Finish</b>                | White           |
| <b>IP Rating</b>                      | IP20            |
| <b>Class Protection</b>               | 2               |
| <b>Internal / External</b>            | Internal        |
| <b>Surface / Recessed / Suspended</b> | Recessed        |
| <b>Diffuser Rating</b>                | Tp(b)           |
| <b>Lifetime (Hrs)</b>                 | L70 B50 54,000h |
| <b>Warranty (Years)</b>               | 2               |
| <b>CE Mark</b>                        | Yes             |
| <b>Diameter (mm)</b>                  | 140 mm          |
| <b>Depth (mm)</b>                     | 38 mm           |
| <b>Accessories</b>                    | ASLED/3NM       |

---

# Technical Information

|                         |               |
|-------------------------|---------------|
| <b>Wattage</b>          | 12W           |
| <b>Lumens Delivered</b> | 1200lm        |
| <b>Lm/W</b>             | 100lm/W       |
| <b>Beam Angle</b>       | 115           |
| <b>CRI</b>              | 80            |
| <b>CCT</b>              | 3000K         |
| <b>Input</b>            | 220/240V      |
| <b>Hertz</b>            | 50/60Hz       |
| <b>Operating Temp</b>   | -15°C to 45°C |
| <b>SDCM</b>             | 6             |
| <b>UGR</b>              | 30            |

Datasheet generated from <https://onetimepim.com> last updated Thursday, October 6, 2022 8:27:02 AM

