



## **ALODLED/150/CW**

Lodi Slim Downlight 150 Cool White



### **Features**

Economic circular LED performance downlight suitable for semi-commercial and residential applications

Low profile design with integral driver

Ideal for use in areas with shallow ceiling voids

Supplied pre-wired with 300mm of cable

## General Information

|                                |                 |
|--------------------------------|-----------------|
| Lamp Type                      | LED             |
| Colour / Finish                | White           |
| IP Rating                      | IP20            |
| Class Protection               | 2               |
| Internal / External            | Internal        |
| Surface / Recessed / Suspended | Recessed        |
| Diffuser Rating                | Tp(b)           |
| Lifetime (Hrs)                 | L70 B50 54,000h |
| Warranty (Years)               | 2               |
| CE Mark                        | Yes             |
| Diameter (mm)                  | 165 mm          |
| Depth (mm)                     | 38 mm           |
| Accessories                    | ASLED/3NM       |

# Technical Information

|                         |               |
|-------------------------|---------------|
| <b>Wattage</b>          | 16W           |
| <b>Lumens Delivered</b> | 1700lm        |
| <b>Lm/W</b>             | 108lm/W       |
| <b>Beam Angle</b>       | 115           |
| <b>CRI</b>              | 80            |
| <b>CCT</b>              | 4000K         |
| <b>Input</b>            | 220/240V      |
| <b>Hertz</b>            | 50/60Hz       |
| <b>Operating Temp</b>   | -15°C to 45°C |
| <b>SDCM</b>             | 6             |
| <b>UGR</b>              | 30            |

Datasheet generated from <https://onetimepim.com> last updated Thursday, October 6, 2022 8:27:02 AM

