



## AMALED80/CCT

Matrix CCT Linklight 800mm



## Features

CCT Selectable LED linklight with integral driver suitable for residential and hospitality applications

Side mounted switch allows installer the choice of 3000K or 4000K colour temperature options

Moulded spine fitted with integral switch and fixed diffuser

c/w angled and straight fixing clips

Supplied c/w 1.5m mains power lead

Linkable up to a maximum of twelve fittings

Non-dimmable

## General Information

<b>Lamp Type</b>	LED
<b>Colour / Finish</b>	White
<b>IP Rating</b>	IP20
<b>Class Protection</b>	2
<b>Internal / External</b>	Internal
<b>Surface / Recessed / Suspended</b>	Surface
<b>Diffuser Rating</b>	Tp(a)
<b>Lifetime (Hrs)</b>	L70 B10 25,000h
<b>Warranty (Years)</b>	4
<b>CE Mark</b>	Yes
<b>Length (mm)</b>	858 mm
<b>Width (mm)</b>	22.8 mm
<b>Depth (mm)</b>	38.4 mm
<b>Accessories</b>	A250TLL/T5, A500TLL/T5, A1000TLL/T5

# Technical Information

<b>Wattage</b>	13W
<b>Lumens Delivered</b>	1300lm (4000K)
<b>Lm/W</b>	102lm/W (4000K)
<b>Beam Angle</b>	100
<b>CRI</b>	80
<b>CCT</b>	3000/4000K
<b>Input</b>	220/240V
<b>Hertz</b>	50/60Hz
<b>Operating Temp</b>	-10°C to 40°C
<b>SDCM</b>	6
<b>UGR</b>	19

Datasheet generated from <https://onetimepim.com> last updated Thursday, October 6, 2022 8:27:05 AM

