



Oxford CCT Surface Linear Multi Wattage 1200mm



- Surface linear suitable for educational and commercial applications
- Modern fully enclosed surface luminaire with curved low profile appearance
- This is a widely used style of fitting within the educational sector
- CCT selectable between 3000K, 4000K and 5000K and power selectable; offering a choice of 2 outputs, in one luminaire
- Steel body with polycarbonate diffuser and plastic end caps
- Dimmable options
- Powered by Philips

Features

Feature 1	Surface linear suitable for educational and commercial applications
Feature 2	Modern fully enclosed surface luminaire with curved low profile appearance
Feature 3	This is a widely used style of fitting within the educational sector
Feature 4	CCT selectable between 3000K, 4000K and 5000K and power selectable; offering a choice of 2 outputs, in one luminaire
Feature 5	Steel body with polycarbonate diffuser and plastic end caps
Feature 6	Dimmable options



Feature 7	Powered by Philips
General Information	
Lamp Type	LED
IP Rating	IP20
IK Rating	IK06
Class Protection	1
Internal / External	Internal
Surface / Recessed / Suspended	Surface
OCTO Category	OCTO options available
Warranty (Years)	5
Material	Polycarbonate,Steel
Technical Information	
Wattage	21W - 32W
Lumens Delivered	2900lm - 5000lm (4000K)
Lm/W	140lm/W
Beam Angle	110
CRI	80
CCT	3000/4000/5000K
Input	220/240V
Hertz	50/60Hz
Operating Temp	-20°C - 40°C
Lumen Depreciation	L80 50,000h
Power Factor	0.9



