



Oxford CCT Surface Linear Multi Wattage 1200mm Microwave Sensor



- Surface linear suitable for educational and commercial applications
- Modern fully enclosed surface luminaire with curved low profile appearance
- This is a widely used style of fitting within the educational sector
- CCT selectable between 3000K, 4000K and 5000K and power selectable; offering a choice of 2 outputs, in one luminaire
- Steel body with polycarbonate diffuser and plastic end caps
- Dimmable options
- Powered by Philips

Features

| | |
|-----------|--|
| Feature 1 | Surface linear suitable for educational and commercial applications |
| Feature 2 | Modern fully enclosed surface luminaire with curved low profile appearance |
| Feature 3 | This is a widely used style of fitting within the educational sector |
| Feature 4 | CCT selectable between 3000K, 4000K and 5000K and power selectable; offering a choice of 2 outputs, in one luminaire |
| Feature 5 | Steel body with polycarbonate diffuser and plastic end caps |
| Feature 6 | Dimmable options |



Feature 7

Powered by Philips

General Information

Lamp Type

LED

Integral Microwave Sensor

Yes

IP Rating

IP20

IK Rating

IK06

Class Protection

1

Internal / External

Internal

Surface / Recessed / Suspended

Surface

Warranty (Years)

5

Material

Polycarbonate,Steel

Technical Information

Wattage

21W - 32W

Lumens Delivered

2900lm - 5000lm (4000K)

Lm/W

140lm/W

Beam Angle

110

CRI

80

CCT

3000/4000/5000K

Input

220/240V

Hertz

50/60Hz

Operating Temp

-20°C - 40°C

Lumen Depreciation

L80 50,000h

Power Factor

0.9



