



## APANLED

Panther CCT Wallpack



## Features

Durable compact wall mounted luminaire for general accent illumination and suitable for industrial applications

All polycarbonate construction ideal for coastal and adverse weather applications

Multiple conduit entry and BESA box fixing points

Selectable CCT between 3000K, 4000K and 6500K output

Supplied c/w optional trim attachment which provides a more commercially aesthetic appearance

Photocell and sensor options

## General Information

Lamp Type	LED
Colour / Finish	Black
Bluetooth Enabled	Yes
IP Rating	IP65
IK Rating	IK08
Class Protection	1
Internal / External	External
Surface / Recessed / Suspended	Surface
Lifetime (Hrs)	L80 B50 60,000h
Warranty (Years)	3
CE Mark	Yes
Width (mm)	255 mm
Height (mm)	305 mm
Depth (mm)	102 mm

# Technical Information

<b>Wattage</b>	25W
<b>Lumens Delivered</b>	2300lm (4000K)
<b>Lm/W</b>	91lm/W (4000K)
<b>Beam Angle</b>	80
<b>CRI</b>	80
<b>CCT</b>	3000/4000/6000K
<b>Input</b>	220/240V
<b>Hertz</b>	50/60Hz
<b>Operating Temp</b>	-10°C to 40°C
<b>SDCM</b>	6

Datasheet generated from <https://onetimepim.com> last updated Thursday, October 6, 2022 8:27:11 AM



