



ASPELED/60/CCT

Spektrum CCT Panel Frame



Features

Minimalist LED panel frame for commercial and architectural applications

Hollow illuminated frame allows installation of standard ceiling panel to sit inside frame and level with grid

Integral switch allows the installer a choice of 3000K, 4000K and 6500K colour temperature options

More decorative option for general illumination

Retains all fire integrity of the ceiling

General Information

Lamp Type	LED
Colour / Finish	Aluminium
Bluetooth Enabled	Yes
IP Rating	IP20
IK Rating	IK06
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Diffuser Rating	Tp(b)
Lifetime (Hrs)	L70 50,000h
Warranty (Years)	3
CE Mark	Yes
Length (mm)	595 mm
Width (mm)	595 mm
Depth (mm)	14 mm

Technical Information

Wattage	27W
Lumens Delivered	3000lm (4000K)
Lm/W	112lm/W (4000K)
Beam Angle	125
CRI	80
CCT	3000/4000/6500K
Input	220/240V
Hertz	50/60Hz
Operating Temp	-20°C to 45°C
SDCM	6
UGR	20

Datasheet generated from <https://onetimepim.com> last updated Thursday, October 6, 2022 8:27:16 AM

