



## Telic CCT Floodlight 50W Black



- Modern slimline LED floodlight with sleek unique design suitable for residential and commercial applications
- Die-cast construction and heat sink design providing optimised thermal characteristics for optimum LED life and performance
- CCT selectable between 3000K, 4000K and 6000K
- Plug and play PIR complete with manual override facility
- Loop-in, loop-out junction back on the rear of the fitting
- Pre-installed breathable gland prevents internal moisture accumulation
- Bracket design allows installation without removing mounting bracket
- Black textured paint finish

### Features

Feature 1	Modern slimline LED floodlight with sleek unique design suitable for residential and commercial applications
Feature 2	Die-cast construction and heat sink design providing optimised thermal characteristics for optimum LED life and performance
Feature 3	CCT selectable between 3000K, 4000K and 6000K
Feature 4	Plug and play PIR complete with manual override facility
Feature 5	Loop-in, loop-out junction back on the rear of the fitting





Feature 6	Pre-installed breathable gland prevents internal moisture accumulation
Feature 7	Bracket design allows installation without removing mounting bracket
Feature 8	Black textured paint finish
General Information	
Lamp Type	LED
IP Rating	IP65
IK Rating	IK06
Class Protection	1
Internal / External	Internal / External
Surface / Recessed / Suspended	Surface
Warranty (Years)	6
Material	Aluminium, Polycarbonate
Technical Information	
Wattage	50W
Lumens Delivered	4600lm (4000K)
Lm/W	98lm/W (4000K)
Beam Angle	90
CRI	80
CCT	3000/4000/6000K
Input	220/240V
Hertz	50/60Hz
Operating Temp	-20°C - 40°C
Lumen Depreciation	L70 60,000h
Power Factor	0.95



