

ATHECO2/CW

Thunder ECO Multi Wattage 600mm Cool White



Features

Robust, high performance LED non-corrosive suitable for ancillary areas and industrial applications

Power selectable; offering high and low output option in each length

Twist off end cap and push fit terminals aid fast and easy installation

Supplied complete with versatile stainless steel mounting clips. Clips can be located anywhere along the spine of the luminaire

Non-Dimmable



Belfast: +44 (0) 2890 773750

General Information

| Lamp Type | LED |
|--------------------------------|---------------------|
| Colour / Finish | White |
| IP Rating | IP65 |
| IK Rating | IK08 |
| Class Protection | 1 |
| Internal / External | Internal / External |
| Surface / Recessed / Suspended | Surface |
| Lifetime (Hrs) | L80 B10 54,000h |
| Warranty (Years) | 3 |
| CE Mark | Yes |
| Length (mm) | 635 mm |
| Width (mm) | 64 mm |

Technical Information

| Lumens Delivered 1200lm - 2100lm Lm/W 121lm/W - 109lm/W Beam Angle 100/140 CRI 80 CCT 4000K Input 220/240V Hertz 50/60Hz Operating Temp -20°C to 40°C SDCM 6 | | |
|--|------------------|-------------------|
| Lm/W 121lm/W - 109lm/W Beam Angle 100/140 CRI 80 CCT 4000K Input 220/240V Hertz 50/60Hz Operating Temp -20°C to 40°C SDCM 6 | Wattage | 10W - 19W |
| Beam Angle 100/140 CRI 80 CCT 4000K Input 220/240V Hertz 50/60Hz Operating Temp -20°C to 40°C SDCM 6 | Lumens Delivered | 1200lm - 2100lm |
| CRI 80 CCT 4000K Input 220/240V Hertz 50/60Hz Operating Temp -20°C to 40°C SDCM 6 | Lm/W | 121lm/W - 109lm/W |
| CCT 4000K Input 220/240V Hertz 50/60Hz Operating Temp -20°C to 40°C SDCM 6 | Beam Angle | 100/140 |
| Input 220/240V Hertz 50/60Hz Operating Temp -20°C to 40°C SDCM 6 | CRI | 80 |
| Hertz 50/60Hz Operating Temp -20°C to 40°C SDCM 6 | ССТ | 4000K |
| Operating Temp -20°C to 40°C SDCM 6 | Input | 220/240V |
| SDCM 6 | Hertz | 50/60Hz |
| | Operating Temp | -20°C to 40°C |
| UGR 27 | SDCM | 6 |
| | UGR | 27 |



Datasheet generated from https://onetimepim.com last updated Thursday, October 6, 2022 8:27:14 AM

