



AVASLED/B

Vasco CCT Bi-directional Suspended Linear 1200mm Black



Features

Aluminium bi-directional suspended pendant suitable for education, commercial and retail applications

Aluminium extruded construction with integral driver

Supplied bi-directional light output as standard with 30% upward light and 70% downward light ratio (directional only option can be selected if required)

Opal diffuser provides optimal light uniformity

Selectable CCT between 3000K, 4000K and 6000K output

Pre-wired with 1.5 metre cable

Adjustable suspension points c/w suspension kit

1-10V dimmable as standard

General Information

Lamp Type	LED
Colour / Finish	Black
IP Rating	IP20
Class Protection	1
Internal / External	Internal
Surface / Recessed / Suspended	Surface,Suspended
Lifetime (Hrs)	L90 36,000h
Warranty (Years)	3
CE Mark	Yes
Length (mm)	1,204 mm
Width (mm)	56 mm
Height (mm)	75 mm
Accessories	AVASLED/LC, AVASLED/90, AVASLED/90/B

Technical Information

Wattage	50W
Lumens Delivered	5300lm (4000K)
Lm/W	105lm/W (4000K)
Beam Angle	105
CRI	80
CCT	3000/4000/6500K
Input	220/240V
Hertz	50/60Hz
Operating Temp	-20°C to 45°C
SDCM	6
UGR	24

Datasheet generated from <https://onetimepim.com> last updated Thursday, October 6, 2022 8:27:15 AM



