



C-Cell 24V 8W IP67 White 6500K 50m



- C-CELL dot-free LED strip suitable for residential, hospitality and retail applications
- Continuous phosphor, uniform dot-free output provides seamless light output for enhanced aesthetic appearance and allows product to be showcased as main lighting source, offering great installation versatility
- Single colour, RGB and tunable white flexible LED strip with self-adhesive back
- Fast fit plug and play connections remove the need for time consuming soldering of joints
- Large strip pack sizes and multiple connector packs offers great time saving and ease when working on a large scale project Joint and connection accessories sold separately
- High CRI 90 ensures the highest quality white light output

Features

| | |
|-----------|---|
| Feature 1 | C-CELL dot-free LED strip suitable for residential, hospitality and retail applications |
| Feature 2 | Continuous phosphor, uniform dot-free output provides seamless light output for enhanced aesthetic appearance and allows product to be showcased as main lighting source, offering great installation versatility |
| Feature 3 | Single colour, RGB and tunable white flexible LED strip with self-adhesive back |
| Feature 4 | Fast fit plug and play connections remove the need for time consuming soldering of joints |



| | |
|--------------------------------|--|
| Feature 5 | Large strip pack sizes and multiple connector packs offers great time saving and ease when working on a large scale project Joint and connection accessories sold separately |
| Feature 6 | High CRI 90 ensures the highest quality white light output |
| General Information | |
| Lamp Type | LED |
| Dimmable | Yes |
| IP Rating | IP67 |
| Class Protection | 3 |
| Internal / External | Internal / External |
| Surface / Recessed / Suspended | Surface |
| Warranty (Years) | 5 |
| Material | Copper, Silicone |
| Technical Information | |
| Wattage | 8W per Metre |
| Lumens Delivered | 776lm/m |
| Lm/W | 97lm/W |
| Beam Angle | 140 |
| CRI | 90 |
| CCT | 6500K |
| Input | 24V |
| Operating Temp | -20°C - 45°C |
| Lumen Depreciation | L70 36,000h |
| Power Factor | 1 |

