

Product Code: AU-LED1624CV

### Features & Applications

- Registered Community Design 001886730 For the supply of low voltage LED lamps
- Short circuit protection Thermal protection 24V DC output 1.0kV SURGE PROTECTION
- Secondary wiring terminals - 3 outputs Loop-in, loop-out primary wiring terminals Integrated earth terminal for earth continuity No junction box required
- Non-dimmable Parallel wiring only 3 Year guarantee



### Full Description

1-16W 24V DC NON-DIMMABLE CONSTANT VOLTAGE LED DRIVER

### Approvals



### Specifications

Input Voltage (V)	100-264V AC 50/60Hz
Output Voltage (V)	24V DC V
Nominal Power (VA)	1-16W VA
Line Current (A)	0.090 A
Sec Current (A)	0.670 A
Power Factor	0.980
Max Ambient Temp (deg. C)	50 deg. C
Max Case Temp (deg. C)	80 deg. C
Case Colour	White Blue Cap
Case Material	Polycarbonate
Protection Class	Class 2
Self Monitoring	<input type="checkbox"/>
Dimmable	<input type="checkbox"/>
SMT	1
Length (mm)	156 mm
Width (mm)	38 mm
Height (mm)	24 mm
Short Circuit Protection	<input checked="" type="checkbox"/>
Overload Protection	<input checked="" type="checkbox"/>
Soft Start	<input checked="" type="checkbox"/>
Primary Connection Type	Screw Terminal - 2 Pairs
Secondary Connection Type	Screw Terminal - 3 Pairs
Guarantee	3 Years
Product Weight	0.094 Kg

*'Passionate about Lighting'*