Product Features:

- Rated to 30, 60 & 90 minute fire ceilings
- Patented LEDchroic™ lens provides halogen appearance with LED efficiency, anti-glare and precise beam control
- 60° lens supplied, interchangeable 40° lens - sold separately
- FastRFix™ rapid install system connector included
- IC cap included
- ErP compliant - High colour rendering index (Ra) >80
- Separate emergency pack available - AU-FRLM10EM
- BS EN 1365-2: 2014 (Fire resistance)
- BS EN ISO 10140-2: 2010 & BS EN ISO 10140-3: 2010 + A1: 2015 (Acoustics)
- (L70) at a 40,000 hour lifetime
- BS EN 13141-1:2004 (Air leakage)
- 5 Year Warranty – see auroralighting.com for details

Product Image:

mPro™ Fixed IP65 Dimmable Fire Rated Downlight

Product Specs:

Technology	LED	**Input Voltage**	220~240V AC
LED Chip	3030	**Number of LEDs**	9
Positional Adjustment	Fixed	**Input Frequency**	50/60HZ
Lifetime L70 (hrs)	40000	**Power Factor**	0.85
Dimmable	Yes	**Luminaire Distribution**	Direct
Positional Adjustment	Fixed	**IP Rating**	IP65
Fire Protection	Yes	**Acoustic Rated**	Yes
SDCM	6	**Operating Temp**	25°C
Optic Material	PMMA	**Overall Diameter (mm)**	88
Cutout Diameter (mm)	72	**Recess Depth (mm)**	100
Weight (Kg)	0.386		

Line Drawing



Polar Curve

60°



40°



SKU Table and Ordering:

Cat No.(SKU Code)	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle
AU-MPRO1/27	7	2700	560	80	60
AU-MPRO1/30	7	3000	600	85.71	60
AU-MPRO1/40	7	4000	640	91.43	60

Compliance & Approvals:

Accessories:

SKU Code	Description
AU-AP600	mPro™ and m10™ Adaptor Plate
AU-BZ600	mPro™ and m10™ Bezel
AU-BZ601	mPro™ and m10™ IP65 Square Bezel
AU-BZ603	mPro™ and m10™ Bezel
AU-BZ605	mPro™ and m10™ Slim Bezel
AU-FRLM10EM	3 Hour Maintained Emergency Pack
AU-LNMPRO40	mPro™ Interchangable 40° Lens

Warranty:

This product has a guarantee period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.