
Technical Datasheet



Product Code: AU-ST324RGB



Features & Applications

• High density RGB colour changing flexible LED strip Twice as many LEDs per 1m as standard LED strip Single RGB LED chip allows programmable settings including static colours and colour changing modes dependant on the control system used IP68 rating allows use in marine/boat applications Any joints/terminations are maximum IP65 Cut point every 100mm 17mm between LED's (SMD5050) Voltage drop of 4V per 5m For runs over 5m individual lengths should be connected in parallel* Very low power consumption - 14.4W per metre Copper track for effective heat dissipation and long life Please order to the nearest metre. Prices per metre (reel length 5m)

Full Description 24V DC IP68 RGB FLEXIBLE HIGH DENSITY LED STRIP LIGHT

100 degs

30000 hrs

60

1 Year

IP68 5000 mm


12 mm

6 mm 24V DC

Yes

Yes

0.074 Kg




Photometric Data


Beam Cone



Specifications

Beam Angle Life hours Number Of LEDs Guarantee **IP** Rating Length Width Height Input Voltage Lamps Included Dimmable Product Weight





Colours

SKU Code Colour AU-ST324RGB RGB

n/a

Lumens Lux MCD Candelas Max Watts Colour Temp n/a n/a n/a 14.4 W n/a

"Passionate about highting"