

Product Features:

- IP65 polycarbonate LED bulkhead
- Life not affected by frequent switching e.g. when used with occupancy controls
- Tough IK10 polycarbonate body and diffuser for maximum impact resistance
- Opal diffuser evenly diffuses light and eliminates LED hot spots
- Wall or ceiling mounting - accessories included
- 20mm conduit side entries
- Emergency and microwave options available
- Adjustable hold time 5 seconds to 30 minutes
- Adjustable light detector from 2-50 lux
- 1.5kV surge protection
- 3 year warranty

Product Image:




UtiliteDrum™ 18W Polycarbonate IP65 Square Drum LED Bulkhead


Product Specs:

| | | | |
|------------------------------|-------|-------------------------------|-------------|
| Technology | LED | Input Voltage | 180~240V AC |
| LED Chip | 2835 | Number of LEDs | 88 |
| Positional Adjustment | Fixed | Input Frequency | 50/60HZ |
| Lifetime L70 (hrs) | 25000 | Power Factor | 0.9 |
| Dimmable | No | Luminaire Distribution | Direct |
| Positional Adjustment | Fixed | IP Rating | IP65 |
| IK Rating | IK10 | SDCM | 5 |
| Operating Temp | 40°C | Optic Material | PC |
| Length (mm) | 255 | Width (mm) | 255 |
| Weight (Kg) | 0.845 | | |

Line Drawing



Polar Curve



SKU Table and Ordering:

| Cat No. (SKU Code) | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour |
|--------------------|---------|--------|--------|-------------|------------|---------------|
| EN-BH18SBLK/40 | 18 | 4000 | 1300 | 72.22 | 120 | Black |
| EN-BH18SBLK/40EM | 20 | 4000 | 1300 | 65 | 120 | Black |
| EN-BH18SBLK/40EMR | 20 | 4000 | 1300 | 65 | 120 | Black |
| EN-BH18SBLK/40MS | 18 | 4000 | 1300 | 72.22 | 120 | Black |
| EN-BH18SW/40 | 18 | 4000 | 1300 | 72.22 | 120 | White |
| EN-BH18SW/40EM | 20 | 4000 | 1300 | 65 | 120 | White |
| EN-BH18SW/40EMR | 20 | 4000 | 1300 | 65 | 120 | White |
| EN-BH18SW/40MS | 18 | 4000 | 1300 | 72.22 | 120 | White |

Compliance & Approvals:



Warranty:

This product has a guarantee period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.