

Product Features:

- Steel housing and high quality polycarbonate diffuser eliminate hot spots providing uniformed low glare light output
- Perfect for retrofitting existing installations or as an alternative to T8 or T5 fluorescent fittings
- Twin version available with winged reflectors for reduced glare
- Through wiring with side and rear cable entry
- Integrated driver supplied in housing
- Available in typical 1200mm, 1500mm and 1800mm lengths
- 1.5kV surge protection
- 3 years warranty

Product Image:




EcoT8™ 1800mm 27W IP20 Single Open T8 LED Batten

Product Specs:

Technology	LED	Input Voltage	220~240V AC
Positional Adjustment	Fixed	Input Frequency	50/60HZ
Lifetime L70 (hrs)	36000	Power Factor	0.95
Dimmable	No	Luminaire Distribution	Direct
Positional Adjustment	Fixed	IP Rating	IP20
IK Rating	IK05	SDCM	6
Operating Temp	55°C	Optic Material	PC
Length (mm)	1820	Width (mm)	55
Weight (Kg)	2.001		

Line Drawing



SKU Table and Ordering:

Cat No.(SKU Code)	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle
EN-BT1827/40	27	4000	2400	88.89	120

Warranty:

This product has a guarantee period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.