

Product Features:

- Multiple sizes and wattages available to suit all new and retrofit installation lighting requirements
- ThermoTec™ technology utilises a combination of highly efficient LED light source, aluminium heat sinking and thermoplastic material for longer life and consistent performance
- Compact integrated driver allows for easy installation
- Life not affected by frequent switching e.g. when used with occupancy controls
- Pre-wired with 500mm 2 core cable
- 1.5kV surge protection
- 3 year warranty

Product Image:




Uni-Fit™ 240V 10W Integrated IP44 Dimmable LED Downlight


Product Specs:

Technology	LED	Input Voltage	220~240V AC
LED Chip	2835	Number of LEDs	30
Positional Adjustment	Fixed	Input Frequency	/50HZ
Lifetime L70 (hrs)	25000	Power Factor	0.8
Dimmable	Yes	Luminaire Distribution	Accent
Positional Adjustment	Fixed	IP Rating	IP44
SDCM	6	Optic Material	PC
Overall Diameter (mm)	120	Cutout Diameter (mm)	90
Recess Depth (mm)	70	Weight (Kg)	0.159

Line Drawing



Polar Curve



SKU Table and Ordering:

Cat No.(SKU Code)	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
EN-DDL10/40	10	4000	710	71	100	White

Compliance & Approvals:



Warranty:

This product has a guarantee period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.