$\Box \Box$

EN-DL29

Project	Comments
Fixture Type	Prepared By

Product Description:

Performance - that's what the Uni-Fit[™] range of commercial downlights stands for. Featuring ThermoTec[™] technology, integrated driver and high quality LED chips to deliver serious lumen performance. The Uni-Fit[™] range is the ideal cost effective solution for new or existing installations where traditional compact fluorescent downlights need upgrading to more efficient LED technology.

Product Image:

Product Specs:



Product Features:

- Multiple sizes and wattages available to suit all new and retrofit installation lighting requirements
- ThermoTec™ technology utilises a combination of highly efficient LED light source, aluminium heat sinking and thermoplastic material for longer life and consistent performance
- Compact integrated driver allows for easy installation
- Life not affected by frequent switching e.g. when used with occupancy controls
- Pre-wired with 500mm 2-core cable .
- 1.5kV surge protection
- 3 year warranty

Compliance & Approvals:



SKU Table and Ordering

Cat. No.	Color	lm	Wattage	Lumens/Watt	Quantity
EN-DL23/64	6400K	1850lm	23W	80.43	
EN-DL23/40	4000K	1800lm	23W	78.26	
EN-DL23/30	3000K	1750lm	23W	76.09	

Warranty:

This product has a warranty period of 3 Years from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, and removal of the Q.C. date label; installation in an improper working environment or installation not according to the current edition of the National Electric Code. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

UK Enlite Sales

16 Alban Park Hatfield Road St. Albans AL4 0JJ

United Kingdom Tel: +44 (0) 1727 83 66 11 Fax : +44 (0) 1727 83 66 22

UK Enlite Distribution

220~240V AC

50/60Hz 0.9

60

Apex Park 6 Little Burrow Welwyn Garden City AL7 4SW

United Kingdom Tel: +44 (0) 1707 35 18 20 Fax : +44 (0) 1727 35 18 21

Input Frequency	50/60Hz
Power Factor	0.9
Dimmable	No
Dimensions	200mm x 70mm (RD)
Number of LEDe	60