

LUMINAIRES - WALL LIGHTS

Product Description:

The WallE[™] range of decorative polycarbonate LED fixtures has been designed to provide subtle accent lighting in both interior and exterior applications. Available in square and rectangular with either an opal diffuser for general lighting, or eyelid variants for pathways. The range is made of fully corrosion resistant polycarbonate, ideal for both residential, commercial and coastal applications.

EN-WL3


Product Image:



4W Polycarbonate IP65 Round Eyelid Wall Light

Product Features:

Line Drawing Image



Product Specs:

Technology	LED	Number of LEDs	14	
Lifetime L70 (hrs)	30000	Input Voltage	220~240V AC	
Input Frequency	50/60HZ	Dimmable	Νο	
Dali	Νο	IP Rating	IP65	
IK Rating	IK10	Operating Env. Temp. (Min) °C	-10	
Operating Env. Temp. (Max) °C	40	Power Factor	0.9	
Overall Diameter (mm)	140	Lamp Base	None	
Surge Protection (kV)	0.5	SDCM	6	

SKU Table and Ordering

SKU Code	Wattage	Lumens	Lumens/Watt	Colour	Beam Angle	Ra	SDCM
EN-WL3/30	4	40	10	3000	50	80	6
EN-WL3/40	4	43	10.75	4000	50	80	6

Compliance & Approvals:



Warranty

This product has a warranty period of 3 Years.

Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

UK Enlite Sales & Distribution Apex Park 6 Little Burrow Welwyn Garden City AL7 4SW United Kingdom Tel : +44 (0) 1707 35 18 20