



### Model TS2000-BST

12V quartz reserve time clock with auto British Summer Time settings.

The TS2000-BST time clock has the facility of automatically adjusting to European/British time settings. Once the user has programmed the date the clock will automatically adjust each spring and autumn. This digital timer is purpose made for access control systems as it operates from a supply voltage of 12v AC/DC. The clock is designed for wall-mounting and its main features are;

- Automatic European Time adjustment
- 12V AC/DC operating voltage
- LCD display
- Quartz crystal timing with reserve
- Daily and weekly programs
- 7 day programming
- 8 on/off periods
- 15 repeat options: day, week, weekend, odd weekdays etc.
- manual override
- switching capacity 10A/30V DC

Dimensions: H = 98mm, W = 66mm, D = 40mm



### Speech unit model 61

This compact unit is fitted to the entrance panel on all our current door entry systems (except as indicated below). The unit provides two-way speech and has an individual volume control for both microphone and speaker. This universal product can be powered from either 12V AC or 12V DC depending on the model of telephone used.

Dimensions: H = 97mm, W = 58mm, D = 24mm



### Speech unit model 51

This unit is generally required as a replacement unit for older systems or for SPA panels above 10 buttons. The unit provides two-way speech and has an individual volume control for both microphone and speaker. This universal product can be powered from either 12V AC or 12V DC depending on the model of telephone used.

Dimensions: H = 136mm, W = 81mm, D = 30mm



### Extension sounders

These units extend the call tone of a door entry telephone to other areas of the premises to improve audibility. The unit is fabricated in white ABS plastic and can be wall mounted in a convenient indoor location. Available models;

Model RT27 for extensions to the standard 801 telephones

Model BS-RT for extensions to the bellissimo telephones

Dimensions: H = 120mm, W = 90mm, D = 38mm



### Sound Generator and extension tone model SG1

Like the models above this unit provides an extension of the call tone on a door entry telephone. In addition to an output of 80 dB at one metre it has 8 user selectable tones. The unit can be triggered either from a 12 Volts source or from a switch.

Dimensions: H = 120mm, W = 90mm, D = 38mm



### Flashing beacon model FB31

This unit gives an effective visual indication of a call at the door entry telephone. This unit is ideal for the 'hard of hearing' or areas with a high level of background noise. The beacon includes a timer circuit that can be set for between 4 and 40 seconds. (A model 212 power supply may be required).

Dimensions: H = 113mm, W = 80mm, D = 60mm



### Flashing beacon model BS-FB (bellissimo)

This unit gives an effective visual indication of a call at the bellissimo door entry video telephone. This unit is ideal for the 'hard of hearing' or areas with a high level of background noise.

Dimensions: H = 113mm, W = 80mm, D = 60mm



### Model LS47 Apartment Station

This wall-mounting unit is ideal for residents who cannot use a telephone such as the elderly or arthritics. It has two large push-button pads; one for speech and one for operating the lock release. Since the unit can only be powered from 12v DC and additional power supply may be required when connecting an existing AC powered system. A model LSD47 desk-mounting version is also available.

Dimensions: H = 95mm, W = 202mm, D = 58mm