LUCECO Tech Data



LED LuxPanel 300mm x 300mm


Edgelit White Frame



- Remote "plug and play" style driver, supplied in standard, dimmable or emergency options
- Maintenance free panel
- Epistar LED and Tridonic Driver

Click here for more information







5 years extended (3 years standard) guarantee and 1 year onsite warranty available in the UK. Rest of the world may vary, please ask your local distributor for more information.




4800K 'neutral white' colour temperature as standard; other colour temperatures available to order, subject to minimum requirement - 3000K / 4000K / 6000K

Cat No	Description	Frame Colour	Voltage	Barcode				
LP30W8S48	Standard driver	White	230V	5015056527130	850	16W	53	700
LP30W8D48	Dimmable driver	White	230V	5015056527154	LUMENS		Lm/W	mA
LED3EP80-0J	Emergency pack	-	-	5015056539089		LED		



Standards			
EN 60598-1	Luminaires - General requirements		
EN 60598-2-2	Luminaires - Recessed		
EN 61347-1	Lamp controlgear - Part 1: General and safety requirements		
EN 61347-2-13	Lamp controlgear - Part 2-13 : Particular requirements for d.c. or a.c. supplied electronic controlgear for LED modules		
EN 55015	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment		
EN 61000-3-2	Electromagnetic compatibility (EMC) - Part 3-2: Limits - Limits for harmonic current emissions		
EN 62471	Photobiological safety of lamps and lamp systems		
2002/96/EC	Waste Electrical & Electronic Equipment (WEEE)		
2011/65/EU	Restriction of the use of certain Hazardous Substances in EEE (RoHS)		
(EC) No 1907/2006	The Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)		
EN 61547	Equipment for general lighting purposes - EMC immunity requirements		



Visit our website at

www.luceco.uk



Supplied by Nexus Industries Ltd Nexus Distribution Centre, Stafford Park 1 Telford, Shropshire, TF3 3BD

