

DECORATIVE WALL LIGHTS + UNDERSHELF LIGHTING

SPECIFICATION SHEET



LED LYTE

Mini LED light

FEATURES

IP rating	IP30
Colour flexibility	Fixed colour
Dimmable	Yes With suitable driver.
Input	350mA
LED Lifetime	70,000h L70 B10
CRI	>80Ra or -
SDCM	3SDCM

INSTALLATION INFORMATION

Cut Out Size	Ø 26mm
Construction Material	Plastic
Weight	20g
Maximum ambient temperature	35°C
Electric Class (1, 2, 3)	3

PHOTOMETRICS @ 25°C

Product code	Wattage	Colour	Beam angle	lm	lm/W	lx @ 1m
LED LYTE NW	1W	4000K	110°	82	82	46
LED LYTE WW	1W	3000K	110°	60	60	30
LED LYTE 27	1W	2700K	110°	58	58	29
LED LYTE AMBER	1W	Amber	110°	-	-	-
LED LYTE BLUE	1W	Blue	110°	-	-	-
LED LYTE RED	1W	Red	110°	-	-	-

WIRING INFORMATION

Cable / Flying Lead	1m (0.205mm ² red & black PTFE)
Type of Wiring Required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/PP/350 1-9 (Plug & Play)	N/A	Yes	No	-	1	9
PLR/350 1-5	N/A	Yes	No	-	1	5
PLD UNI-DRIVE 350mA	N/A	Yes	Yes (1-10V)	-	1	10


ACCESSORIES


LED LYTE 1M EXT	1m Plug & Play extension lead
LED LYTE 6 WAY EXT	6-way 1m Plug & Play extension lead
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types




COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

 /collingwoodlighting

 /collingwoodlighting

 collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Plug & Play connector for quick installation

Small & discreet

Ideal for decorative lighting

Beam angle: 110°

