

DECORATIVE WALL LIGHTS + UNDERSHELF LIGHTING

SPECIFICATION SHEET



MF02 IP

Adjustable LED mini light

FEATURES

IP rating	IP65
Colour flexibility	Fixed colour
Tilttable	45°
Rotation angle	360°
Dimmable	Yes With suitable driver
Input	350mA
LED Lifetime	70,000h L70 B10
CRI	>80Ra or -
SDCM	3SDCM

INSTALLATION INFORMATION

Cut Out Size	N/A
Bathroom zone	1
Inrush Current	N/A
Construction Material	Stainless steel (316)
Weight	90g
Maximum ambient temperature	35°C
Electric Class [1, 2, 3]	3

PHOTOMETRICS @ 25°C

Product code	Wattage	Colour	Beam angle	lm	lm/W	lx @ 1m
MF02 IP NW	1W	4000K	16°	66	66	452
MF02 IP WW	1W	3000K	16°	53	53	252
MF02 IP 27	1W	2700K	16°	52	52	245
MF02 IP AMBER	1W	Amber	16°	-	-	-
MF02 IP BLUE	1W	Blue	16°	-	-	-
MF02 IP GREEN	1W	Green	16°	-	-	-
MF02 IP RED	1W	Red	16°	-	-	-

WIRING INFORMATION

Cable / Flying Lead	0.15m (0.205mm² red & black PTFE)
Type of Wiring Required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	N/A	Yes	No	1	1	9
PLR/350 1-5	N/A	Yes	No	1	1	5
PLD UNI-DRIVE 350MA	N/A	Yes	Yes (1-10V)	2	1	10


ACCESSORIES


WB/M 01 / WB/M 02	Single bracket / double bracket
CR135	PTFE cable
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types
UY2 CONNECTOR	Quick waterproof connector



COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

 /collingwoodlighting

 /collingwoodlighting

 collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Mini spot light for discreet illumination

Can be used for interior and exterior applications

Can be rotated and angled to direct light

Beam angle: 16°

