

Dual Tariff Double Stacked Consumer Unit Datasheet MCU28/TIS/W, MCU36/TIS/W



Construction and Features

- Dual Tariff Consumer Unit arrangement with 2 Isolators
- Powder coated gloss white
- All steel construction
- 40mm tail entry knockouts
- Dual Tariff Consumer Unit arrangement with 2 Isolators
- Compliments an RCBO arrangement of up to 24 RCBOs (MCU28/TIS/W)
- Compliments an RCBO arrangement of up to 32 RCBOs (MCU36/TIS/W)
- Featuring two lids both with Lumo® LED feature
- Accessory pack includes battery, labels & instructions
- BS7671 18th Edition Compliant / Regulation 421.1.201
- Multi knockouts all around the unit including the rear
- Plenty of room for cabling making it easier to install
- Earth contact points for added safety
- Locks as standard
- 5-year warranty

Technical Data

- MCU28/TIS/W - 24 Way Dual Tariff Consumer Unit with 2 x 100A Main Switches
- MCU36/TIS/W - 32 Way Dual Tariff Consumer Unit with 2 x 100A Main Switches
- Compatible with: ROH & ROM RCBOs, MD, MC & MH MCBs, IS2100 Main Switch
- Rated Current: 100A
- Neutral Bars x 2
- Earth Bars x 2
- Isolator: 100A DP EN60947-3 x 2
- Busbar: Floating Insulated Pin Type 100A
- Internal Links: Sleeved flexible heat pressed terminated copper braid
- Third Party Tested to EN61439-3 by Intertek

Overall & Installation Dimensions

