

## Modular Timer Datasheet MODT15D - 7-day Digital Timer

### Construction and Features

- 2 Module Width
- Electronic with LCD display
- Switch Loads up to 16A
- 7 day 24 hour ON/OFF programming
- Permanent ON/OFF switching
- Battery back up

### Technical Data

- Type: Electronic with LCD Display
- Rated voltage: 230V AC
- Rated frequency: 50/60Hz
- Contact: 1NO+1NC
- Consumption: maximum 4VA
- Contact capacity:
  - 16A/250V AC (COS  $\Phi$  = 1)
  - 25A/250V AC (COS  $\Phi$  = 0.6)
- Incandescent lamp: 1000W
- Electrical endurance:  $10^5$  cycles
- Mechanical endurance:  $10^7$  cycles
- Time basis: quartz
- 24 hours+ week program
- Working Precision:  $\leq 2$  sec/day (25° C)
- Min. programmable interval: 1 minute
- Power reserve: min. 15 days
- Ambient temperature: -10-40°C
- Humidity: 35-85% RH
- Connection terminal: pillar terminal with clamp
- Connection capacity: rigid conductor 6mm<sup>2</sup>
- Installation: On symmetrical DIN rail or panel mounting



### Wiring Diagram

N/A

### Overall & Installation Dimensions

