



General Information

Material number	98307
Type	recessed light
Product segment	Indoor
Theme	sonstige / nicht zuordenbar

Dimensions

Article Height (in mm)	42
Article Diameter (in mm)	88
Installation Depth (in mm)	50
Cutout (in mm)	68
Net Weight	0 Kilogram

Material & Colour

Enclosure Material	aluminium
Enclosure Colour	satın nickel

Functionality

Switch Type	without switch
Function	LED not replaceable
Battery	No

Technical Information

Protection Degree	IP20
Protection Class	2
Mains Voltage	220-240V,50/60Hz
Operation Voltage	220-240V,50/60Hz
Dimmable	Yes
max. Wattage (1)	6W

Illuminant 1

Beamangle (in °)	50
Nominal Luminous Flux (in lm)	450
Equivalence With Incandescent Lamp (W)	60
Colour Temperature	4000K neutral white
Nominal Lifetime (in h)	15000
Switching Cycles	100000
Colour Rendering Index (Ra, CRI)	>80
Energy Efficiency Class	A+
Rated Lamp Power (0,1W precision)	6
Colour Tolerance (LED, SDCM)	<6

Compatible Dimmers

ABB - 6523 UJGL-214P

BERKER - 2873

BERKER - 8542 12 00

BUSCH-JAEGER - 2247 U

BUSCH-JAEGER - 6523 U

BUSCH-JAEGER - 6524 U

CLIPSAL - 32E450UDM

ELTAKO - EUD61NPN

GIRA - 2262 00/I00

GIRA - 238500/I00

JUNG - 225 NV DE

LEGRAND - 400T

LEGRAND - 7759 03

SCHALK - ETD U2

SIEMENS - 5TC8 256

SIEMENS - 5TC8 263

SIEMENS - 5TC8 284

SIEMENS - 5TC8211-0

VADSBO - VD100

98307 SALICETO

