



## Features

- Suitable for internal and external use.
- 3 hour maintained version available for 5ft 60W & 6ft 65W versions.
- Microwave sensor available on 5ft 60W version.
- Easy install and wiring.
- 5 year warranty.

Product Codes	
HY4-30W	4FT 30W
HY5-30W	5FT 30W
HY5-60W	5FT 60W
HY5-60W-EM	5FT 60W 3hr Maintained Emergency
HY5-60W-MW	5FT 60W Microwave Sensor
HY6-65W	6FT 65W
HY6-65W-EM	6FT 65W 3hr Maintained Emergency

Technical Specification	
Fitting Type	SMD LED Anti Corrosive Baton
Voltage	180-240V 50/60Hz
Wattage	30W / 60W / 65W
Lumens	30W – 2700lm 60W – 5400lm 65W – 5850lm
Colour Temperature	4000K
CRI	80
Class	I
IP Rating	IP65
Finish	Grey base, Opal diffuser
Dimmable	No
Mounting	Surface
Certificate	CE & ETL
Impact Rating	IK08
Sensor	Microwave (HY5-60W-MW)
Emergency	3 hour maintained at 3W 270lm (HY5-60W-EM & HY6-65W-EM only)
Dimensions Width & Depth	100mm x 70mm