

'CORVUS' - LED Range - IP65 Non-Corrosive Luminaires

- + Polycarbonate frosted diffuser, Polycarbonate base, metal gear tray
- + Single & Twin fittings in 2 lengths
- + Available in Emergency Fittings
- + Fitting includes LED driver
- + Tamper proof screws
- + Metal latching clips for diffuser

Emergency Fittings

	ACPLEDS5	ACPLEDT5	ACPLEDS6	ACPLEDT6	ACPLEDS5EM	ACPLEDT5EM	ACPLEDS6EM	ACPLEDT6EM
Power Rating	220V-240V AC ~50Hz							
Barcode	5012739648427	5012739648434	5012739648441	5012739648458	5012739648465	5012739648472	5012739648489	5012739648496
Wattage	30W	60W	40W	80W	30W	60W	40W	80W
Length	5ft		6ft		5ft		6ft	
Power Rating	230V AC ~50Hz							
Lumens Output	3300	6600	4400	8800	3300	6600	4400	8800
No of Clips	12							
Class	Class 1							
IP Rating	IP65							
Beam Angle	120°							
Operating Range	-20°C - +40°C							
Main Housing	Polycarbonate frosted diffuser, Polycarbonate base							
Dimensions	L1532 x W85 x H78	L1532 x W104 x H78	L1794 x W85 x H78	L1794 x W104 x H78	L1532 x W85 x H78	L1532 x W104 x H78	L1794 x W85 x H78	L1794 x W104 x H78
Fixing Centres	950mm		1000mm		950mm		1000mm	
Colour Temperature	5,000K							
SDCM	<6							
Battery Type	n/a				Ni-Cd 6V, 2Ah			
Ballast Type	LED driver							
Knockout Size	20mm							
No of Knockouts	6	6	8	8	6	6	8	8
CRI	>80							
Power Factor	>0.9							
Life Expectancy	30,000 hrs							
Guarantee	3 Years							
Conforms To	EN60598-1 & BSEN60598-2-1							

