

### Service Connector Blocks

Heavy duty blocks for use of meter/mains position



- ▶ **Black urea phenolic**
- ▶ **Easy knocked entries**
- ▶ **Lids can be sealed for security**

TECHNICAL INFORMATION	
Voltage:	230V AC
Operating Temp:	-10 - +40°C
Conforms:	BS EN 60998-1 BS EN 60998-2-1

	Part No	Description	Product Information	Pk Qty
	<b>CB1</b>	Connector Block 100A 25mm <sup>2</sup>	Single pole, 5 way 132g, H64 x W47 x D38mm	20
	<b>CB2</b>	Capacity 5 cables per pole	Double pole, 2 x 5 way 290g, H89 x W65 x D55mm	10
	<b>CB3</b>	Connector Block 100A 35mm <sup>2</sup>	Single pole, 5 way 188g, H64 x W47 x D38mm	20
	<b>CB6</b>	Capacity 5 cables per pole	Double pole 2 x 5 way 493g, H104 x W66 x D67mm	10
	<b>CB9</b>	200A 70mm <sup>2</sup> Capacity 6 cables	Single pole, 6 way 585g, H125 x W64 x D55mm	1

- ▶ **ABS Plastic**
- ▶ **Steel Screws**
- ▶ **Easy knocked entries**
- ▶ **Lids can be sealed for security**

TECHNICAL INFORMATION	
Voltage:	230V 50Hz
Operating Temp:	-10 - +40°C
Conforms:	EN 60998-1 EN 60998-2-1

	Part No	Description	Product Information	Pk Qty
	<b>CB35S</b>	Connector Block 100A, 25mm <sup>2</sup> 1 x 5 way	Single pole, 132g L64.5 x W47.1 x H37mm	20
	<b>CB35D</b>	Connector Block 100A, 35mm <sup>2</sup> 2 x 5 way	Double pole, 188g L103.7 x W68.6 x H68mm	10