

TWIN SPOTS - NON-MAINTAINED

Powerful Twin Spot Non-Maintained fittings for defined escape routes in interior (ELTSLED20NM) and exterior (ELTSLED65NM) applications. Ideal for use in warehouses, factories, long corridors and high bay industrial applications.

- Adjustable heads
- Individual LED lamp health indicators
- Emergency operation duration 3 hours
- Fused main terminals



ELTSLED65NM



ELTSLED20NM

	ELTSLED65NM	ELTSLED20NM
Product Finish	White	White
Description	LED Twin Spot	LED Twin Spot
Wattage	5.4W Total	5.2W
IP Rating	IP65	IP20
Product Dimensions	H290 x W300 x D70mm	H308.5 x W280 x D55.5mm
Product Weight	1630g	1143g
Barcode	5012739633898	5012739638343
IP Rating	IP65 Rated	IP20 Rated
Lumens Output (Emergency mode)	Battery - 590 lm	Battery - 385 lm
Battery Type	3.6V/6Ah Ni-Cd	3.6V 4.5Ah Ni-Cd
Voltage	230V AC ~ 50Hz	
Main Housing Material	Polycarbonate body	
Charge Time	24 hours	
Guarantee	3 Years	
Certification & Conformity	BS EN 60598-1 / BS EN 60598-2-22	