

- Steel body construction, Opal polycarbonate diffusers
- Intergrated driver
- High output options in the same footprint
- High LED chip efficiency
- Instant start
- Compact design



	<i>LEDBAT4</i>	<i>LEDBAT5</i>	<i>LEDBAT6</i>	<i>LEDBAT4H</i>	<i>LEDBAT5H</i>	<i>LEDBAT6H</i>
Description	4ft Batten	5ft Batten	6ft Batten	4ft Batten (High Output)	5ft Batten (High Output)	6ft Batten (High Output)
Product Dimensions	L1190 x W53 x H64mm	L1485 x W53 x H64mm	L1758 x W53 x H64mm	L1190 x W53 x H64mm	L1485 x W53 x H64mm	L1758 x W53 x H64mm
Product weight	1030g	1281g	1510g	1106g	1342g	1674g
Barcode	501273645839	501273645853	501273645877	501273645846	501273645860	501273645884
Wattage	18W	24W	32W	36W	48W	64W
Lumens	1800	2400	3400	2900	4000	5200
Mounting Options	BESA mount or Screw fixings					
Lamp Type	LED Non-replaceable					
IP Rating	IP20					
Knockouts	2 x 20mm at ends of fitting and 1 x 20mm at the back of fitting					
Colour Temperature	4,000K					
Beam Angle	120°					
Class Type	1					
Main housing material	Steel Body with Polycarbonate Diffuser					
Guarantee	3 Years					
Certification & Conformity	BS EN - 60598					

TECHNICAL DATA SHEET

