

This range of LED striplights add subtle downlighting to your home. Ideal for mounting under kitchen units, shelves, wardrobes, display cabinets, alcoves and much more. These striplights simply click together, no tools required.

- Available in Cool White 4,000K and Warm white 3,000K
- Can combine 10 LED & 20 LED fittings
- Fittings can be close butted or linked with adjustable link lead
- A selection of accessories are available such as dimmers and photocells. Please see back for details
- Suitable for indoor use only



The Maximum number of fittings in one run:-

DRIVERS	35cm	60cm
LED125D (Supplied with starter kit)	6	3
LED250D (Sold separately)	10	6

	STARTER KITS	ADD ON KITS 2 X 35CM	ADD ON KITS 1 X 60CM
	LED125D-C (Warm White) LED250D-C (Cool White)	LED125D-2N-C (Warm White) LED250D-2N-C (Cool White)	LED125D-60N-C (Warm White) LED250D-60N-C (Cool White)
Contents	2 x 35cm LED Striplights, 1 x 30cm Link Lead, 8 x crimps, 2 x Female Connectors, 2 x Male Connectors, 8 x Mounting Clips & Screws, 1 x In-line LED Driver	2 x 35cm LED Striplights, 2 x 30cm Link Lead, 8 x crimps, 2 x Female Connectors, 2 x Male Connectors, 8 x Mounting Clips & Screws	1 x 60cm LED Striplights, 1 x 30cm Link Lead, 8 x crimps, 2 x Female Connectors, 2 x Male Connectors, 8 x Mounting Clips & Screws
Product Dimensions	Length 345 x Dia 12mm		Length 588 x Dia 12mm
Product weight	0.312g	0.168g	0.193g
Barcode	LED125D-C - 5012739 644054 LED250D-C - 5012739 644085	LED125D-2N-C - 5012739 644061 LED250D-2N-C - 5012739 644092	LED125D-60N-C - 5012739 644078 LED250D-60N-C - 5012739 644108
Cable Length	Input - 1.2m/Output - 2.1m	-	-
Lumens	Per 35cm Strip = 150 lm		Per 60cm Strip = 300 lm
Lamp Type	LED		
Lamp life expectancy	25,000 hrs		
LED's Array	10		20
Colour Temperature	Cool White - 4,000k Warm White - 3,000k		
Input Voltage	12V DC		
Power Consumption	2.8W per 35cm strip		4.5W per 60cm strip
Main housing material	Aluminium		
Guarantee	3 Years		
Certification & Conformity	BS EN 60950-1		


These easy plug-in accessories for the LED Striplight Range enable local control of light level.




LEDPCN



LEDPIRN



LEDDIMN



LEDLEADN



LEDD125D / LED250D

	LED125D	LED250D	LEDDIMN	LEDPCN	LEDPIRN	LEDLEADN
Contents	LED DRIVER The Maximum number of fittings in one run:- 6 x 35cm or 3 x 60cm	LED DRIVER The Maximum number of fittings in one run:- 10 x 35cm or 6 x 60cm	In-line Dimmer	In-line photocell	In-line PIR	Link Lead
Product Dimensions	Input lead 1.2M Output lead 2.1M	Input lead 1.2M Output lead 2.1M	Cable length each side 15cm	Cable length each side 15cm	Cable length each side 15cm	30cm
Product weight	0.163g	0.200g	0.057g	0.058g	0.055g	0.008g
Product Information	-	-	IP20	IP20	Max Range 5M On time 4 mins max	-
Barcode	5012739644276	5012739644283	5012739644344	5012739644368	5012739644375	5012739644351
Rated Current	1250mA	2500mA	2.5A	2.5A	2.5A	-
Input Voltage	230V	230V	12V DC	12V DC	12V DC	
Guarantee	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year
Certification & Conformity	EN 60950-1		-	-	-	-