# GREEN BROOK

# 'Orion' Range - ODM202

# Microwave Presence Detector - Programmed Settings

- Suitable for LED and energy saving lamps
- Detection range 360°/180°
- Adjustable time delay
- Pre-set ambient light settings
- Microwave sensor





### "Suitable for incorporation into light fittings"

# "Accurate level settings"

TECHNICAL INFORMATION	
Rated Voltage:	230V~50Hz
IP Rating:	IP20
Ambient Light:	2 LUX, 5 LUX, 20 LUX,
	50 LUX, 2000 LUX (choice)
Transmission Power:	<0.2mW
HF System:	5.8GHz CW radar, ISM band
Hold Time:	5s, 30s, 1min, 5min, 10min,
	20min, 30min (choice)
Rated Load:	Max 1200W _8-
	Max 300W 🦾 /LED
Detection Range:	Ceiling 360° / Wall 180°
Detection Distance:	Wall = 5 - 15M adj
	Ceiling = 1 - 8M (radius) adj
Power Consumption:	0.9W approx
Installation Height:	Wall = 1.5 - 3.5M
	Ceiling = 2 - 8M
Detection Moving Speed: 0.6 - 1.5m/s	
Detection Area:	10%, 30%, 50%, 75%, 100% choice
Dimensions:	63.5 x 37 x 25mm







#### www.greenbrook.co.uk