

MECHANICAL THERMOSTATS

Our range of mechanical thermostats also includes two froststats and a cylinder/pipe stat. These mechanical thermostats are easy to install and have an IP rating of IP20.

- 3 wire operation



TH90-C



TH90C-C



TH90T-C



TH90F-C



TH90FT-C



TH90CS-C

	TH90-C	TH90C-C	TH90T-C	TH90F-C	TH90FT-C	TH90CS-C
Product Finish	White					
Description	Break on rise	Changeover contact	Tamperproof Changeover contact	Froststat - For frost protection of building fabric, contents and exposed pipework Break on rise	Froststat Tamperproof - For frost protection of building fabric, contents and exposed pipework Changeover contact	Cylinder/Pipe Stat - Control for boilers and central heating Changeover contact
Product Dimensions	H83 x W83 x D34mm					H120 x W40 x D40mm
Product weight	90 gms		81 gms	90 gms	81 gms	220 gms
Barcode	5012739640407	5012739640414	5012739640452	5012739640438	5012739640445	5012739640421
IP Rating	IP20					
Class	II					
Operating Temperature	+5°C to +35°C			-5°C to +15°C		+20°C to +90°C
Voltage	230V AC					
Max Load	Resistive 10A opening	Resistive 10A opening, 3A closing	Resistive 10A opening,	Resistive 10A opening	Resistive 10A opening,	Resistive 15A opening, 15A closing
Guarantee	1 Year					
Certification & Conformity	EN 60730-1/ EN 60730-2-7					