DATASHEET



2 gang 13A Double Pole Switched Socket with 2 USB

Code: 71SS2USBULTPB-W

Hartland | HARTLAND RANGE | USB Power Sockets

Insert Type

Product Class 1

Temperature

Ambient Operating

Standard/Approval


Recommended Location

Maximum Installation Altitude 2000m


Product Image



Wiring



Dimensions



	Outlets 2x2.4A (4.8A Total)
Insert Colour	Polished Brass/White
EAN13 Barcode	5017504089955
Commodity Code	85363010
Luckins TSI	405688535
Dimensions(Nominal)	Double: Height = 88.0mm Width = 144.5mm Depth = 5.0mm
Weight	241 GR
Switched Poles	Double
Current Rating	13 Amp, USB 2 x 2.4A
Voltage	180/250V AC USB = 5V
Maximum Load	13 Amp, USB = 2.4A X 2
Mains Frequency	50/60Hz
IP Rating	IP2XD
Contact Gap Minimum	3mm
Terminal Capacity 1	3x2.5mm²
Terminal Capacity 2	3x4mm²
Terminal Capacity 3	2x6mm² Multi-Strand
Earth Terminal Capacity 1	3x2.5mm²
Earth Terminal Capacity 2	3x4mm²
Earth Terminal Capacity 3	2x6mm² Multi-Strand

Must be earthed

-15°C to +40°C

Internal Use Only

BS1363 BS EN 62368

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonyille Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

120 6

E: info@hamilton-litestat.com | **W:** www.hamilton-litestat.com

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. This datasheet was expected in 2/28/2023 11:03.73 AM ESOF.