
## DATASHEET

## Code: 723XLEDITB100

## Hartland | HARTLAND RANGE | LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmers


## **Product Image**



Wiring



Dimensions



Insert Type	3 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer
Insert Colour	Satin Brass
EAN13 Barcode	5017504079208
Commodity Code	85365015
Luckins TSI	403373570
Dimensions(Nominal)	Double: Height = 88.0mm Width = 144.5mm Depth = 5.0mm
Switched Poles	Single
Current Rating	0.3A Per Gang
Voltage	230V AC
Maximum Load	5-70W Per Gang
Mains Frequency	50Hz
IP Rating	IP2XD
Terminal Capacity 1	2X1mm²
Terminal Capacity 2	2X1.5mm²
Terminal Capacity 2 Earth Terminal Capacity 1	2X1.5mm² 5x1mm²
Earth Terminal Capacity 1	5x1mm <sup>2</sup>
Earth Terminal Capacity 1 Earth Terminal Capacity 2	5x1mm <sup>2</sup> 4X1.5mm <sup>2</sup>
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3	5x1mm <sup>2</sup> 4X1.5mm <sup>2</sup> 3X2.5mm <sup>2</sup>
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4	5x1mm <sup>2</sup> 4X1.5mm <sup>2</sup> 3X2.5mm <sup>2</sup> 1X4mm <sup>2</sup> Multi-Strand
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5	5x1mm <sup>2</sup> 4X1.5mm <sup>2</sup> 3X2.5mm <sup>2</sup> 1X4mm <sup>2</sup> Multi-Strand 1X6mm <sup>2</sup>
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating	5x1mm² 4X1.5mm² 3X2.5mm² 1X4mm² Multi-Strand 1X6mm² Face plate muct be earthed
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature	5x1mm <sup>2</sup> 4X1.5mm <sup>2</sup> 3X2.5mm <sup>2</sup> 1X4mm <sup>2</sup> Multi-Strand 1X6mm <sup>2</sup> Face plate muct be earthed -5°C to +40°C
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location	5x1mm <sup>2</sup> 4X1.5mm <sup>2</sup> 3X2.5mm <sup>2</sup> 1X4mm <sup>2</sup> Multi-Strand 1X6mm <sup>2</sup> Face plate muct be earthed -5°C to +40°C

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

**T:** +44 (0)1747 860088

E: info@hamilton-litestat.com | W: www.hamilton-litestat.com

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. This datasheet was generated on 2/28/2023 11:43:21 AM E&OE